

BoB ASSISTANT *Predictive maintenance assistant*



The sensor analyzes the vibration signature of an industrial equipment, ensuring its remote monitoring. The data is transmitted via a public or private LoRaWAN® radio frequency network.

APPLICATIONS

- Supervision of industrial installations equipped with motors (pumps, ventilation, cooling unit, ...)
- Optimization of maintenance operations

BENEFITS & FEATURES

- LoRaWAN®, Class A
- Easy to install and ease of use
- > 2 years of autonomy
- Measuring ranges / accuracies :
 - Vibration: 0-400Hz / ± 6Hz and 0-12.4kHz / ± 200Hz
 - Temperature: -20°C to +55°C / ± 1°C

CERTIFICATION

- RoHS, CE



*Photo not contractual

The sensor monitors the vibration signature of an equipment (pump, ventilation, etc...) on the ranges 0 to 400Hz (± 6Hz) and 0 to 12.4kHz (± 200Hz) every 5 minutes (adjustable).

After an automatic learning period of 7 days, the sensor alerts in case of vibration drift, allowing maintenance teams to intervene before a breakage or failure. The data transmission on public or private LoRaWAN® network is done periodically or immediately in case of alert:

- Exceeding the vibration drift threshold (adjustable)
- Machine on/off (adjustable)

Installation and commissioning is quick and easy.

The sensor is equipped with:

- A button for activation and deactivation,
- An RGB LED to monitor configuration and association on the network,
- 2 magnets facilitating the installation of the sensor on the equipment (also possible by gluing, riveting, screwing...).

Each sensor is identified by a QR code on the label.

The data pre-processed by the on-board artificial intelligence is gathered in a report transmitted on the LoRaWAN® network every 180 minutes.

The sensor periodically reports the machine's operating time over the last 180 minutes, the rate of vibration drift recorded over this period, the battery level, the temperature, and a predictive failure probability.

Machine status alerts (Start/Stop) are also available (can be inhibited by Downlink control).

Powered by a 3.6V/2000mAh battery, the autonomy of the sensor is more than 2 years with a configuration of 8 transmissions per day.

THE LARGEST IOT PRODUCTS RANGE FOR YOUR PROJECT

WATTECO is a European leader in the design and manufacture of intelligent IoT devices to fit to all remote reading and data collection solutions.

WATTECO is a LoRa Alliance®.

TECHNICAL SPECIFICATIONS

RADIO FREQUENCY		
Frequency	EU: 863-870 MHz	
Transmitted power	+14 dBm	
Sensitivity	-137 dBm	
FIRMWARE		
Protocol	LoRaWAN®, Class A	
Sampling frequency	5 minutes (configurable)	
Transmission interval	Every 180 minutes	
Data compression	None	
Activation method	Over-The-Air Activation (OTAA)	
Data encryption	AES128	
MEASURES		
	Vibration	Temperature
Beach	Low frequency: 0 - 400Hz High frequency: 0 - 12800Hz	-20°C to +55°C
Accuracy	± 6Hz (0 - 400Hz) and ± 200Hz (0 - 12800Hz)	± 1°C
ALARMS		
Vibration	Vibration drift of 25% by default (configurable as Downlink at 10, 15 or 20%)	
State	Switching on / off (status frames can be inhibited by downlink control)	
POWER SUPPLY		
Voltage	Lithium battery 3.6V / 2000mAh on holder (battery can be changed after removing the cover) Transmitted battery voltage level in steps of 0.1V	
Autonomy (within a range of +10°C to +25°C)	> 2 years: 2 samples (low frequency and high frequency) every 5 minutes and 8 transmissions per day	
USER INTERFACE		
Push button + RGB LED	Association in the network; sensor status visible via lexan	
BOX		
Dimensions / weight - Sealing	76x79xep.23mm / 75grs - IP68	
Fixation	2 magnets and 2 nuts (supplied)	
TEMPERATURE		
How it works	-20°C / +55°C+0%rH / +95%rH (non-condensing)	
Storage	+10°C / +30°C+0%rH / +60%rH	
STANDARDS & REGULATIONS		
CE: EN 301489-3 V2.1.1, EN 61000-6-2:2005, EN 300-220-2 V3.1.1, 2014/53/UE(RED), EN 60950-1:2006, EN60950-22:2006, EN62479:2008 RoHS (2011/65/EU)		

PRODUCT REFERENCE



REFERENCE	DESCRIPTION
50-80-001	BoB ASSISTANT EU 868 MHz SENSOR